

### Switcher 4/1 VGA/Audio VGA/3,5mm stereo plug

- In a desktop case with integrated power supply
- Operation via front side keyboard or RS-232
- 15pin Sub-HD-females / 3,5mm stereo plug
- Bandwidth 300MHz
- Optional 19" mountable
- Adjustable priority function



Front



Backside

#### Technical data

Dimensions (W x H x D)	483mm x 44mm x 115mm
Power supply	230V/50Hz; Fuse 100mA
Connectors	15 pin SUB-HD & 3,5mm stereo plug
Operating temperature	5 – 45°C

#### VGA

##### Input

Number of VGA	4
Input impedance	75Ω
Input coupling	DC

##### Output

Output impedance	75Ω
------------------	-----

#### Frequenzy response

300MHz	-3dB
Gain	0dB

#### Audio

##### Input

Number of	5
Input impedance	>10Ω
Input coupling	AC

##### Output

Anzahl	1
Output impedance	50Ω

#### Frequenzy response

20Hz up to 18KHz

#### Operation Behavior

adjustable via software	Volume in 61 steps (0 up to 61) Bass (-7 bis +7) Treble (-7 bis +7)
-------------------------	---

#### RS232 Interface

Baud rata	9600 Baud
Data-Bit	8
Parity-Bit	None
Stopp-Bit	1

#### Consumption

10W

Type	Item No.
Switcher 4/1 VGA/Audio VGA/3,5mm stereo plug	06002048